

**JURONG ISLAND – SEMBAWANG UTILITIES PTE LTD & CHEVRON
CHEMICAL (FAR EAST) PTE LTD**

JETTY	DEPTH ALONGSIDE (m)	APPROACH DEPTH (m)	MAX LOA (m)	MAXIMUM DISPLACEMENT (tons)
OSAK3	13.2	12.2	223	60,000
OSAK4	14.5	12.5	180	50,229

GENERAL INFORMATION

1. No berthing of vessel above the maximum displacement.
2. Communication : Pilot Walkie Talkie - P05
: Operation room number - OSAK3 : +65-6267 5687
- OSAK4 : +65-6263 2588

PILOTAGE GUIDELINES

BERTHING and UNBERTHING (DAY AND NIGHT)

No tidal restriction

TUG GUIDELINES

TUG RECOMMENDATION FOR BERTHING AND UNBERTHING @:
Berth Name (OSAK3 & OSAK4)

LENGTH OVERALL OF VESSEL	NUMBER OF TUGS
Up to 70 metres LOA	Pilot to consult master on the use of tug and, if required, order from the tug company nominated by the agent
71 to 122 metres LOA	1 small tug
123 to 152 metres LOA	2 small tugs
153 to 180 metres LOA	2 medium tugs
181 to 220 metres LOA	2 big tugs

221 to 280 metres LOA	2 big tugs (Pilot may order additional tug)
-----------------------	---

Revised: 20 Dec 2013