

ATLANTIS SHIPYARD (YA)

BERTH	DEPTH A/S (m)	APPROACH DEPTH (m)	LENGTH OF BERTH (m)	REMARKS
YAFD 1 NEPTUNE DOCK	-	5.4	155	width - 24m
YAD1E NEPTUNE DOCK EAST QUAY	7.4	5.4	155	
YAD1W NEPTUNE DOCK WEST QUAY	8.1	5.4	155	
YAFD 2 FLOATING PONTOON	-	5.4	116	width - 23m
YAD2E FLOATING PONTOON EAST QUAY	5.7	5.4	116	
YAD2W FLOATING PONTOON WEST QUAY	8.2	5.4	116	
YAQA QUAY 'A'	3.2	5.4	155	
YAQB QUAY 'B'	5.4	5.4	155	
YAQC QUAY 'C'	5.2	5.4	125	

PILOTAGE GUIDELINES

1. DOCKING/UNDOCKING (DAY)

No restriction

2. BERTHING/UNBERTHING (DAY)

No restriction

3. NO NIGHT MOVEMENT

TUG GUIDELINES

TUG REQUIREMENT FOR SHIPYARD MOVEMENTS

1. The table provides for the number of tugs to be assigned to a vessel when berthing/unberthing or shifting at the shipyard.
2. For vessels proceeding to a Floating Dock or Graving Dock, the shipyard may assign an additional tug.
3. For jack-up oil rigs, 3 suitable big tugs are recommended and for semi-submersibles 4 suitable big tugs are recommended.
4. The pilot may in consultation with the master, cancel or order additional tugs if necessary. For vessels equipped with a suitable thruster in good working condition, one tug at that position may be dispensed with.
5. The shipyard may arrange its own tugs for the movement. Please consult the respective shipyard for advice when ordering tugs.

LENGTH OVERALL OF VESSEL	NUMBER OF TUGS FOR VESSELS WITH ENGINES	NUMBER OF TUGS FOR VESSELS UNDER TOW
Up to 60 metres LOA	1 small tug	2 small tugs
61 to 100 metres LOA	2 small tugs	3 small tugs
101 to 130 metres LOA	1 small and 1 medium tug	2 small and 1 medium
131 to 150 metres LOA	2 medium tugs	1 small and 2 medium tugs
151 to 180 metres LOA	2 medium tugs	3 medium tugs
181 to 200 metres LOA	1 medium and 1 big tug	3 medium tugs
201 to 260 metres LOA	1 medium and 2 big tugs	2 medium and 2 big tugs
More 260 metres LOA	3 big tugs	2 medium and 3 big tugs

Revised: 20 Dec 2013